

➤ TABLE OF STANDARD PROPERTIES OF USE AND MEASUREMENT

The properties defined in the table below, are set up according to the technical conditions of use and measurement. These properties are warranted within their variation range and in compliance with the standard technical conditions of use.

Properties TT60SM	Standard technical conditions	Unit	Nominal values	Min. values	Max. values
Notes		-	-	-	-
Sensor options	SG	-	-	-	-
Mastered motions	TZ, RX	-	-	-	-
TZ max. no load displacement	Quasistatic excitation, blocked-free	μm	80	72	92
RX Angular displacement		mrad (+/-)	11.00	9.90	11.39
TY displacement		μm	25.00	22.50	28.75
Blocked force	Quasistatic excitation, blocked-free	N	110	88	132
Stiffness	Quasistatic excitation, blocked-free	N/μm	2.00	1.60	2.20
Unloaded resonance frequency (in the actuation's direction)	Harmonic excitation, blocked-free, on the admittance curve	Hz	3000	2550	3300
Response time	Quasistatic excitation, blocked-free	ms	0.17	0.15	0.19
Capacitance (per electrical port)	Quasistatic excitation, free-free, on the admittance curve	μF	1.55	1.40	2.02
Angular resolution		μrad	0.11	-	-
Vertical resolution		nm	0.80	-	-
Height		mm	18.00	17.95	18.05
Length		mm	25.00	24.95	25.05
Width		mm	13.00	12.95	13.05
Mass		g	65.0	-	-
Standard mechanical interface (payload)	Flat surface 2.5*8 mm ²	-	-	-	-
Standard mechanical interface (frame)	2 M2 threaded holes	-	-	-	-
Standard electrical interface	4 PTFE insulated AWG30 wires 100 mm long with Ø1 banana plug	-	-	-	-

➤ PROPERTIES STANDARD TECHNICAL CONDITIONS OF USE AND MEASUREMENT

Free-free	: The actuator is not fixed
Blocked-free	: The actuator is fixed to a mechanical support assumed infinitely stiff
Quasistatic excitation	: AC voltage between -20 and 150 V at 1 Hz
Harmonic excitation	: Voltage of 0.5 Vrms, sinusoidal mode from 0 to 100 kHz
Max. harmonic excitation	: Voltage defined by the measurement of max. displacement, sinus at resonance frequency
Displacement measurement	: Laser interferometer, capacitive displacement sensor
Admittance measurement	: HP 4194 A or Cypher C60 electrical impedance analyser
Environment	: Ambient temperature (15-25°C) and dry air (Humidity < 50 % rH)

Any technical conditions of use, different from those defined above, can lead to temporary or definitive alterations of properties. Thank you to contact CEDRAT TECHNOLOGIES before using actuators under non standard technical conditions.

➤ FACTORY TESTS CARRIED OUT

- Test 1 : Electrical admittance vs. Frequency, free-free
- Test 2 : Displacement vs. input voltage

➤ EXTRA FACTORY TESTS

- Test 3 : Gain and linearity of the sensor
- Test 4 : Step response in closed loop
- Test 5 : Stability in closed loop

➤ MECHANICAL INTERFACE

- | | | |
|--|---|---|
| <input type="checkbox"/> [FI] Flat Interface | <input type="checkbox"/> [H] Flat Interface with hole | <input type="checkbox"/> [TH] Flat Interface with threaded hole |
| <input type="checkbox"/> [SV] Specific version | <input type="checkbox"/> [FF] Free-free Interface | <input type="checkbox"/> [SI] Specific interface |

➤ AVAILABLE OPTIONS

- | | | |
|--|--|--|
| <input checked="" type="checkbox"/> [SG] Strain gauges | <input type="checkbox"/> [ECS] Eddy Current Sensor | <input type="checkbox"/> [NM] Non-magnetic |
| <input checked="" type="checkbox"/> [VAC] Vacuum | | |