

➤ TABLE OF STANDARD PROPERTIES OF USE AND MEASUREMENT

The properties defined in the table below, are set up according to the technical conditions of use and measurement. These properties are warranted within their variation range and in compliance with the standard technical conditions of use.

Properties PPA10M	Standard technical conditions	Unit	Nominal values	Min. values	Max. values
Notes		-	-	-	-
Max. no load displacement	Quasistatic excitation, blocked-free	μm	8	7	12
Blocked force	Quasistatic excitation, blocked-free	N	800	640	960
Stiffness	Quasistatic excitation, blocked-free	N/μm	100,00	80,00	110,00
Resonance frequency (free-free)	Harmonic excitation, free-free, on the admittance curve	Hz	65000	55250	71500
Response time (free-free)	Harmonic excitation, free-free, on the admittance curve	ms	0,01	0,01	0,01
Capacitance	Quasistatic excitation, free-free, on the admittance curve	μF	0,70	0,63	0,91
Max. tensile force	Static effort, blocked-free	N	400	300	400
Resolution	Quasistatic excitation	nm	0,08	-	-
Height (in actuation direction)		mm	18,00	17,80	18,20
Depth (base)		mm	10,00	9,90	10,10
Width (base excl. wedge & wires)		mm	6,50	5,50	7,50
Width (base incl. wedge & wires)		mm	9,00	8,00	10,00
Mass		g	6,0	-	-
Standard mechanical interface (top)	1 centered M2.5 threaded hole 2.5 mm deep	-	-	-	-
Standard mechanical interface (base)	1 centered M2.5 threaded hole 2.5 mm deep	-	-	-	-
Standard electrical interface	2 PTFE insulated AWG30 wires 100 mm long with Ø 1 banana plug	-	-	-	-

➤ PROPERTIES STANDARD TECHNICAL CONDITIONS OF USE AND MEASUREMENT

Free-free	: The actuator is not fixed
Blocked-free	: The actuator is fixed to a mechanical support assumed infinitely stiff
Quasistatic excitation	: AC voltage between -20 and 150 V at 1 Hz
Harmonic excitation	: Voltage of 0.5 Vrms, sinusoidal mode from 0 to 100 kHz
Max. harmonic excitation	: Voltage defined by the measurement of max. displacement, sinus at resonance frequency
Displacement measurement	: Laser interferometer, capacitive displacement sensor
Admittance measurement	: HP 4194 A or Cypher C60 electrical impedance analyser
Environment	: Ambient temperature (15-25°C) and dry air (Humidity < 50 % rH)

Any technical conditions of use, different from those defined above, can lead to temporary or definitive alterations of properties. Thank you to contact CEDRAT TECHNOLOGIES before using actuators under non standard technical conditions.

➤ FACTORY TESTS CARRIED OUT

- Test 1 : Electrical admittance vs. Frequency, free-free
- Test 2 : Displacement vs. input voltage

➤ EXTRA FACTORY TESTS

- Test 3 : Gain and linearity of the sensor
- Test 4 : Step response in closed loop
- Test 5 : Stability in closed loop

➤ MECHANICAL INTERFACE

- | | | |
|--|---|--|
| <input type="checkbox"/> [F1] Flat Interface | <input type="checkbox"/> [H] Flat Interface with hole | <input checked="" type="checkbox"/> [TH] Flat Interface with threaded hole |
| <input type="checkbox"/> [SV] Specific version | <input type="checkbox"/> [FF] Free-free Interface | <input type="checkbox"/> [SI] Specific interface |

➤ AVAILABLE OPTIONS

- | | | |
|--|---|--|
| <input checked="" type="checkbox"/> [SG] Strain gauges | <input type="checkbox"/> [ECS] Eddy current displacement sensor | <input checked="" type="checkbox"/> [NM] Non-magnetic sensor |
| <input checked="" type="checkbox"/> [VAC] Vacuum | | |